

GS 4000 BROCHURE

JUNHO 2013

Tel: (+351) 21 843 64 00
Fax: (+351) 21 843 64 09
geral@bhb.pt www.bhb.pt

Capital Controls®

GS4000 Chlorine Dioxide Generator

The Capital Controls GS4000 chlorine dioxide generator from Severn Trent Services offers a simple and effective means of generating a low strength Chlorine Dioxide solution. The GS4000 is capable of generating between 2g/day to 10g/hr in a single system using two commercially available reagents, hydrochloric acid (8.5%) and sodium chlorite (7.5%).

Features

- Ranges in size from 2g/day to 10g/hour
- Safe on-demand production of chlorine-free chlorine dioxide
- Simple, reliable operation
- Fully automatic or manual option
- Low maintenance

Applications



Potable Water

- Primary Disinfection
- Total THM Reduction
- Iron and Manganese Removal



Cooling Water

- Broad Spectrum Biocide
- Action without pH Constraints and Corrosion Problems



Food and Beverage Processing

- Microbiological Control at Low Concentrations without Taste and Odour



Wastewater

- Chemical and Pesticide Oxidation / Reduction
- Odour Control in Scrubber Systems
- Bacteria Control



Building Services Water Hygiene

- BISRIA Recommended for the Control of Legionella in Hot and Cold Water Systems





Paper Industry

- Bacteria Control in Paper Machines

Ultra Pure Water

- Destroys Biofilm in Process Pipework Systems



OPERATING DESCRIPTION

Chlorine dioxide is generated by the reaction of two commercially available reagents, hydrochloric acid (8.5%) and sodium chlorite (7.5%). Two peristaltic pumps control the automatic addition of the two reagents into a reaction tower where the chlorine dioxide is generated. The solution is then diluted to a 1g/l solution with carrier water as it flows from the reaction tower into a storage chamber. The storage vessel section is vented to atmosphere via a carbon filter which removes any residual chlorine dioxide vapours.

The microprocessor automatically controls the chlorine dioxide generation process from reagents filling, dilution and storage. Capable of accepting a START/STOP commands the system is capable of remote operation. The controller also accepts up to four digital inputs from external alarms such as reagent level sensors.

TECHNICAL SPECIFICATION

Production Capability	2 g/day up to 10 g/hr
Chlorine Dioxide concentration	1 g/l as Chlorine Dioxide
Ambient Temperature	5 - 45°C
Power Requirements	230Vac \pm 10%, 50 hz
Max power consumption	50 VA
Weight	24 kg
Dimensions	800mm High x 600mm Wide x 150mm Deep

Controller

Protection	IP65
Display	16+16 characters LCD, with back light
Digital Inputs	8
Digital Outputs	8
Standard Alarms	System Running/System Failed/System Alarm
Chlorine Dioxide Pump Control	Start/Stop signal
External alarm inputs	up to 4

Connection Details

Water Inlet	½" BSP(F)
Solution Outlet	½" BSP(F)
Drain	½" BSP(F)
Vent	10 x 12mm Poly tubing connection

Materials of Construction

Backboard	uPVC
Reaction tower and storage chamber	uPVC
Internal tube & Fittings	Teflon/PVDF/PVC/PE

Represented by:

--

Contactos/Contacts:

Comercial/Commercial:

Fernando Mena Costa

e-mail: fcosta@bhb.pt

Tel: (+351) 21 843 64 00

Fax: (+351) 21 843 64 09

Assistência/Service:

Patricia Costa

e-mail: ppcosta@bhb.pt

Tel: (+351) 21 843 64 00

